

SUPERFLEX®

XP3016 - 50cm wide

Superflex is our thinnest material at between 50-60 microns. It's mild sticky backing makes intricate designs quick and simple to produce. With a very large colour range Superflex is ideal for multi colour transfer layering.

A4 samples are available free of charge upon request, for larger samples 1m rolls are available to purchase.

STEP BY STEP

STEP 1

Cut your design in mirror image. Film blade required.

STEP 2

Weed away any excess material.

STEP 3

Place transfer face down onto the garment with the transparent backing on top and press for 10 seconds at 150°C.

STEP 4

Remove the transparent backing cold.

DURABILITY

80°C

MICRONS

50-60

FINISH

Semi Matt

TACK

Mild

PEEL

Cold

PU OR PVC

PU

PRODUCT INFORMATION

SIZE: 50cm wide x 1m, 5m, 20m rolls

CUTTING FORCE: Film blade (0.25) from 30gf *

TRANSFER LAYERING: Yes (excluding metallics)

SUITABLE FOR

COTTON

POLYESTER

POLY/COTTON

ACCREDITATIONS

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100
HIGHEST LEVEL WITH
Tested for harmful substances.
www.oeko-tex.com/standard100

CLASS 1



TRANSFER SETTINGS

TIME	10 seconds (Re-press for 5 seconds if multi layering)
TEMP	150°C
PRESSURE	Medium
PEEL	Cold

CARE INFORMATION

WASH UP TO 80°C (Up to 40°C inside out for multi layering)

CAN BE DRY CLEANED

CAN BE TUMBLE DRIED

DO NOT IRON

STORAGE (Store vertically in a dry room between 15-30°C)

* All force testing has been undertaken using a NEW blade on a Roland GS24. The force will increase with the age of the blade, therefore always test prior to use.

PLEASE NOTE: The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Superflex shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Superflex has been tested using Kustom Kit garments, when applying to other garment brands results may vary, testing prior to purchase is recommended.