



INSTRUCTION & INFORMATION

GLOSSY FLEX

XP3051 - 50cm wide

Glossy Flex has a high gloss finish making it ideal for eye-catching effects.

A4 samples are available free of charge upon request, for larger samples 1m rolls are available to purchase.

STEP BY STEP

STEP 1

Cut your design in mirror image. Film blade required.

STEP 2

Weed away any excess material.

STEP 3

Place transfer face down onto the garment with the transparent backing on top and press for 15 seconds at 160°C.

STEP 4

Peel the transparent backing warm waiting 5-10 seconds.

DURABILITY	MICRONS	FINISH	TACK	PEEL	PU OR PVC
60°C	100	Gloss	Medium	Warm	PU

PRODUCT INFORMATION

SIZE: 50cm wide x 1m, 5m, 25m rolls

CUTTING FORCE: Film blade (0.25) from 60gf *

TRANSFER LAYERING: No

SUITABLE FOR

COTTON

POLYESTER

POLY/COTTON

ACCREDITATIONS



TRANSFER SETTINGS

TIME	15 seconds
TEMP	160°C
PRESSURE	Light/Medium
PEEL	Warm (wait 5-10 seconds)

CARE INFORMATION

UP TO 60°C INSIDE OUT

CAN BE DRY CLEANED

CAN BE TUMBLE DRIED

DO NOT IRON

STORAGE (Store vertically in a dry room between 15-30°C)

* All force testing has been undertaken using a NEW blade on a Roland GS24. The force will increase with the age of the blade, therefore always test prior to use.

PLEASE NOTE: The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Glossy Flex shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Glossy Flex has been tested using Kustom Kit garments, when applying to other garment brands results may vary, testing prior to purchase is recommended.



Web: www.xpres.co.uk Support www.xprestechnical.co.uk

Oakridge Park, Trent Lane, Castle Donington, Derby DE74 2PY Phone: 01332 855 085 E-mail: sales@xpres.co.uk